

# Highly Efficient, Durable Cathodes for Solid Oxide Fuel Cells (SOFCs)

---

## Facilitates fuel cell performance across a broad temperature spectrum

This technology was developed to provide faster oxygen-reduction reactions (ORR) in solid oxide fuel cells (SOFCs) while maintaining durability. It dramatically enhances ORR kinetics and stability of current lanthanum strontium cobalt ferrite (LSCF) cathodes by applying an efficient electro-catalyst coating derived from a low-cost, one-step infiltration process. The coating is a conformal perovskite nickel manganese (PNM) film and highly active praseodymium oxide nanoparticles exsolved from the PNM film. The nanoparticles exhibit high oxygen vacancy concentrations that facilitate rapid ORR kinetics. The PNM film provides rapid oxygen ion transport to the LSCF surface and, in addition, enhances the stability of the cathode.

This well-designed approach to introducing a thin catalyst on a cathode backbone provides high performance and excellent stability and facilitates improved SOFC performance across a broad temperature spectrum.

## Summary Bullets

- **More stable:** The technique used enhances cathode durability while maintaining the high-kinetic electrode structure
- **Stackable:** The cathode design is suitable for implementation in a fuel cell stack
- **Fast:** The combination of nanoparticles and conformal coatings provides increased reaction sites and rapid transport paths

## Solution Advantages

- **More stable:** The technique used enhances cathode durability while maintaining the high-kinetic electrode structure
- **Stackable:** The cathode design is suitable for implementation in a fuel cell stack
- **Fast:** The combination of nanoparticles and conformal coatings provides increased reaction sites and rapid transport paths

## Potential Commercial Applications

- Solid oxide fuel cells
- Distributed energy generation

- Energy conversion
- Energy storage
- Electrolysis cells

## Background and More Information

Solid oxide fuel cells offer clean and efficient energy generation; however, their adoption is hindered by limited lifetime and high cost to fabricate and operate. One way to lower their cost is to enhance the ORR, particularly at lower temperature. Resistance during ORR contributes the most to energy loss in current SOFCs, and the problem is more pronounced at lower temperatures. The Georgia Tech innovation addresses these issues.

## Inventors

- Dr. Meilin Liu  
Regents' Professor & Associate Chair - Georgia Tech School of Materials Science and Engineering
- Dr. Dong Ding  
Former Postdoctoral Fellow - Georgia Tech
- Dr. Yu Chen  
Postdoctoral Research Associate - Georgia Tech Meilin Liu Lab
- Lei Zhang  
Visiting Research Student - Georgia Tech Department of Biomedical Engineering


## IP Status

The following patent has issued, and additional international coverage is pending: US11018346B2

## Publications

[A Robust and Active Hybrid Catalyst for Facile Oxygen Reduction in Solid Oxide Fuel Cells](#), Energy and Environmental Science - March 14, 2017

## Images



Visit the Technology here:

[Highly Efficient, Durable Cathodes for Solid Oxide Fuel Cells \(SOFCs\)](https://s3.sandbox.research.gatech.edu/print/pdf/node/3374)

---

<https://s3.sandbox.research.gatech.edu/print/pdf/node/3374>