

Fuel Cell Membranes That Operate at High Temperature (#4346)

A thermally and mechanically stable polymer electrolyte membrane for use in fuel cells

Georgia Tech inventors have developed a thermally and mechanically stable polymer electrolyte membrane for use in fuel cells. The fuel cell PEM contains a porous support film with fibers, a layer of free acid, and a polysiloxane polymer bonded to the film and both sides of the layer of free acid. Membranes may contain single or multiple layers that are laminated before use in a fuel cell. The tri-layer PEMs have been adapted to operate at low humidity and at high temperatures with minimal loss of conductivity. A key feature is a skin layer that is molecular-level grafted phosphonic acid polysiloxane, while the central layer consists of free acid doped with heterocycle grafted polysiloxane. This design inhibits free acid leakage from the central layer due to repulsion of the same-charge carrier in the central and skin layers. The PEMs may be synthesized by sol-gel process, spraying methods, or similar methods.

Benefits/Advantages

- High conductivity at high temperature and low humidity
- **Mechanically stable** — PEMs do not tear or deform under normal operating conditions
- **Reduced acid leaching** — unique acid doping between layers reduces leaching, which prolongs the life of the fuel cell

Potential Commercial Applications

- Proton exchange membrane fuel cells
- Electrochromic cells
- Capacitors
- Electrochemical devices

Background/Context for This Invention

Fuel cells are in high demand as alternative energy sources due to their lower emission and higher energy profiles. They operate by electrochemical reactions, where a positively charged electrode and a negatively charged electrode are separated by a membrane. Polymer electrolyte membranes or proton exchange membranes (PEMs) are used in many fuel cell designs; however, some are difficult and costly to synthesize, and others experience conductivity loss due high temperatures or low relative humidity. In

addition, some may experience acid leaching when operated at high temperatures.

John Muldoon

Senior Research Scientist - Georgia Tech School of Materials Science and Engineering

Zhen Zhou

PhD student - Georgia Tech School of Materials Science and Engineering

Dr. Meilin Liu

Regents' Professor & Associate Chair - Georgia Tech School of Materials Science and Engineering

Xiaobing Zhu

Postdoc - Georgia Tech School of Materials Science and Engineering

More Information

Publications

For more information about this technology, please visit:

<https://licensing.research.gatech.edu/technology/fuel-cell-membranes-operate-high-temperature>

Images:

The automated sequential delivery of multiple fluids. A varying number of delay gates imprinted in the branches are shown in the figure.

COVID-19 and flu saliva test on paper: (A) The automatic sequential delivery of multiple reagents required for virus test; (B) Water pouring into the device triggers the virus assay, allowing the presence of SARS-CoV-2 and influenza A & B viruses to be visually identified by the color changes in the corresponding detection spot

