

Piezoelectric Nanowire Based Hearing Aids (#4222)

A mechanism which merges the miniature of nanowire structure and the piezoelectricity of ZnO to function as a hearing aid

Georgia Tech inventors have created a mechanism which merges the miniature of nanowire structure and the piezoelectricity of ZnO. The device mimics the mechanism of how a hair cell works, which could potentially be applied as an advanced category of hearing aid device option. This invention includes a vibration sensor and a substrate. A first electrical contact and a spaced apart second electrical contact are both disposed on a first surface of the substrate. The elongated piezoelectric nano-scale structure extends outwardly from the first surface of the substrate and is disposed between, and in electrical communication with, the first electrical contact and the second electrical contact. The elongated piezoelectric nano-scale structure is oriented so that a voltage potential exists between the first electrical contact and the second electrical contact when the elongated piezoelectric nano-scale structure is bent from a first state to a second state.

Benefits/Advantages

- Smaller size
- More power efficient

Potential Commercial Applications

- Hearing aids

Background/Context for This Invention

One out of ten people suffer from hearing loss worldwide, constructively and sensorineurally. People are affected in various ways, from mild impairment to profound deafness, and affecting both children and adults. Hearing aid devices offer people with hearing loss a significant way to improve the quality of their life. The majority of hearing loss falls in the sensorineural hearing loss (SNHL) category, which is normally caused by damage to inner hair cells, outer hair cells, which then causes a cochlear malfunction. The typical device for addressing SNHL uses digital signal processing for preprocessing of the sound signals. However, these devices have drawbacks such as a relatively large size and high power consumption.

Dr. Zhong Lin Wang

Former Hightower Chair, Regents' Professor - Georgia Tech School of Materials Science and

Engineering; Distinguished Professor - Georgia Tech College of Engineering

Changshi Lao

Student – Georgia Tech School of Materials Science and Engineering

More Information

U.S. Number: 8,758,217

Publications

For more information about this technology, please visit:

<https://licensing.research.gatech.edu/technology/piezoelectric-nanowire-based-hearing-aids>

Images:

The automated sequential delivery of multiple fluids. A varying number of delay gates imprinted in the branches are shown in the figure.

COVID-19 and flu saliva test on paper: (A) The automatic sequential delivery of multiple reagents required for virus test; (B) Water pouring into the device triggers the virus assay, allowing the presence of SARS-CoV-2 and influenza A & B viruses to be visually identified by the color changes in the corresponding detection spot

