

# A Process to Chemically Modify Polymeric Materials

---

## A process that chemically modifies polymeric materials through static, low-pressure infiltration

Inventors at Georgia Tech have advanced a process called Vapor Phase Infiltration (VPI) that requires only a single exposure cycle to convert microns of polymer into a hybrid material. VPI can chemically modify a variety of polymeric materials in a variety of form factors using low-pressure, highly reactive gases. This technology utilizes the following steps: sorption, diffusion, and entrapment. During sorption, a gaseous metalorganic precursor is dissolved into a polymer. The precursor then migrates during the diffusion step. In entrapment, the precursor is immobilized through reaction or steric hindrance.

### Summary Bullets

- **Cost reduction** – cost is reduced due to technique simplification
- **Efficiency** – technique has no requirement for repeated cycling
- **Flexibility** – VPI can be applied at any stage in production processes

### Solution Advantages

- **Cost reduction** – cost is reduced due to technique simplification
- **Efficiency** – technique has no requirement for repeated cycling
- **Flexibility** – VPI can be applied at any stage in production processes
- **Increased reliability** – chemical properties are more stabilized

### Potential Commercial Applications

#### Manufacturing for:

- Polymer Membranes
- Polymer Fabrics / Textiles
- Polymer Films
- Polymer Foams
- Bulk Polymers
- Polymer Powders / Microspheres

### Background and More Information

Atomic Layer Deposition (ALD) is a surface-controlled process that results in the deposition of thin films one layer at a time. Each atomic layer that is formed by this sequential process is a result of saturated surface-controlled reactions. In ALD, increasing processing volume presents significant challenges to the fluid dynamics in the chamber, with unpredictable effects on the quality of the film deposition. Additionally, long cycle times and the layer-by-layer nature of ALD result in slow deposition rates. There is a need to develop a more efficient process to modify polymeric materials.

## Inventors

- Dr. Mark Losego  
Assistant Professor - Georgia Tech School of Materials Science and Engineering
- Brandon Piercy  
Georgia Tech School of Materials Science and Engineering
- Collen Z. Leng Leng  
Graduate Student – Georgia Tech School of Materials Science and Engineering


## IP Status

: US10364491B2

## Publications

, -

## Images



Visit the Technology here:

[A Process to Chemically Modify Polymeric Materials](#)

---

<https://s3.sandbox.research.gatech.edu/print/pdf/node/3440>