

Integrated Force Sensing for Probe Microscopy

Several modifications to probe microscopy and force spectroscopy techniques

Georgia Tech inventors have developed several modifications to probe microscopy and force spectroscopy techniques. One of the inventions disclosed is a class of sensors where a simple micromachined membrane structure is used to measure the tip displacement directly, and in a broad band manner eliminating the corruption of this information by the cantilever. Another disclosed technology involves the use of integrated large range electrostatic or piezoelectric actuators that replace the cantilever and the actuator that drives the cantilever previously described, with an integrated actuator which may have a much broader bandwidth. Additionally, for the first time, a complete FIRAT based Probe Microscope System has been disclosed to be used for material characterization, fast nanoscale imaging and imaging biological and chemical fluid samples.

Summary Bullets

- Optimization of the optical detection sensitivity in air or liquid
- Mini AFM configuration able to form images in very small volumes
- Multi-tip nanosensors with simultaneous, multifunctional capabilities

Solution Advantages

- Optimization of the optical detection sensitivity in air or liquid
- Mini AFM configuration able to form images in very small volumes
- Multi-tip nanosensors with simultaneous, multifunctional capabilities
- Integrated actuator and a robust sensitive probe

Potential Commercial Applications

- Life sciences
- Material science
- Semiconductors
- Proteomics
- Drug discovery
- Biomedical
- Defense

Background and More Information

Inventors

- ## IP Status

Publications

Images



Integrated Force Sensing for Probe Microscopy

